## **18" Ductless Fume Hood**

## Model # SS-218-DCH

The **18" Wide Ductless Fume Hood** helps protect the operator and environment from hazardous fumes or particulate generated from applications performed within the hood. The compact design makes it an ideal fume extraction solution for containing beakers and test tubes in chemical and/or biological labs or even for small-scale pharmaceutical compounding applications. This lightweight hood provides optimal fume control for field-testing applications because of its ability to be easily transported and its reliable operation. Also as an option, this system can include a removable spill tray for chemical spills.

The **18" Ductless Fume Hood's** powerful fan directs fumes into the filter chamber containing high quality filter media selected depending on the application. Filter media choices include **HEPA** [up to 99.97% efficiency on particles 0.3 microns and larger], **ASHRAE** [up to 95% efficiency on particles 0.5 microns and larger, **Activated Carbon**, and **specialty-blended filtration** [i.e. acid gas, mercury, aldehyde, and ammonia].

Typical uses for the **18" Ductless Fume Hood** include chemical fumes, pharmaceutical compounding, soldering applications, dust removal, biological applications, and a variety of applications requiring fume and dust removal. The **18" Ductless Fume Hood** can provide an effective and economical solution for many commercial, medical, laboratory and industrial applications that require a small containment area.

Our line of ductless fume hoods is not intended for sterile compounding applications.





18" Ductless Fume Hood



18" DCH provides fume control for a variety of laboratory applications.

## **Product Features**

- Includes: clear anti-static vinyl curtains and LED light
- Optional: variable speed controller (115V only), hour counter, velometer, and spill tray
- **Standard Sizes:** 12", 18", 24", 30", 40", 50", 60", and 70" (custom sizes available)
- Quiet operation
- · Long filter life
- · Simple, quick "no tool" filter change
- Portable and lightweight
- Reliable, low maintenance operation



## **Product Specifications**





Shown with outer dimensions. Dimensions are approximate.



21221 FM 529 Rd Cypress, TX 77433 1.800.799.4609 sales@sentryair.com

www.sentryair.com

Hood Dimensions (D x W x H)  Recess Area: 8" x 18" x 18" Access Area: 8" x 18"  Sides: 0.25" white acrylic Base: 0.5" white high density polyethylene  Top: 0.5" clear polycarbonate  Front Window: 0.25" clear polycarbonate  Blower Dimensions  Blower Material  Front Window: 0.25" clear polycarbonate  Blower Material  Blower Material  10.5"L x 8" W x 8.5" H  16 Ga. carbon steel with polyester epoxy coating on all surfaces  Weight (approximately)  Air Volume (approximately)  Air Volume (approximately)  Carbon Pre-filter + HEPA Filter - 100 FPM Carbon Pre-filter + Heavy Duty Carbon Filter - 60 FPM  115/1/60, 0.3 amps 220/1/50, 0.2 amps 8' grounded power cord with NEMA 5-15P plug  Sound Level  Maximum  Temperature  Temperature  No perating temperature not to exceed 170° F  HEPA (up to 99.97% efficient on particles down to 0.3 microns)  ASHRAE (up to 95% efficient on particles down to 0.3 microns)  ASHRAE (up to 95% efficient on particles down to 0.5 microns)  ACTIVATED ACTIVATE		
Hood Material  Base: 0.5" white high density polyethylene Top: 0.5" clear polycarbonate Front Window: 0.25" clear polycarbonate  Blower Dimensions  10.5"L x 8" W x 8.5" H  16 Ga. carbon steel with polyester epoxy coating on all surfaces  Weight (approximately)  Air Volume (approximately)  Carbon Pre-filter + HEPA Filter - 100 FPM Carbon Pre-filter + Heavy Duty Carbon Filter - 60 FPM  115/1/60, 0.3 amps 220/1/50, 0.2 amps 8' grounded power cord with NEMA 5-15P plug  Sound Level  Maximum Temperature  Main Filter Options  Base: 0.5" white high density polyethylene Top: 0.25" clear polycarbonate  Top: 0.25" clear polycarbonate  10.5"L x 8" W x 8.5" H  16 Ga. carbon steel with polyester epoxy coating on all surfaces  Waring temperature  Negrounded power cord with NEMA 5-15P plug  Ficient on particles down to 0.3 microns)  ASHRAE (up to 99.97% efficient on particles down to 0.3 microns)  ASHRAE (up to 95% efficient on particles down to 0.5 microns)  Activated Carbon  Specialty-blended Filter Media (i.e. acid gas, mercury, aldehyde, and ammonia)  Limited two-year warranty from date of shipment on		<b>Interior:</b> 18" x 18" x 18"
Blower Material  Blower Material  16 Ga. carbon steel with polyester epoxy coating on all surfaces  Weight (approximately)  Air Volume (approximately)  Inlet Velocities on High (approximately)  Electrical  Carbon Pre-filter + HEPA Filter - 100 FPM Carbon Pre-filter + Heavy Duty Carbon Filter - 60 FPM  115/1/60, 0.3 amps 220/1/50, 0.2 amps 8' grounded power cord with NEMA 5-15P plug  Sound Level  Maximum Operating temperature not to exceed 170° F  HEPA (up to 99.97% efficient on particles down to 0.3 microns)  ASHRAE (up to 95% efficient on particles down to 0.5 microns)  ASHRAE (up to 95% efficient on particles down to 0.5 microns)  Activated Carbon Specialty-blended Filter Media (i.e. acid gas, mercury, aldehyde, and ammonia)  Limited two-year warranty from date of shipment on	Hood Material	Base: 0.5" white high density polyethylene Top: 0.5" clear polycarbonate Front Window: 0.25"
Blower Material   polyester epoxy coating on all surfaces	<b>Blower Dimensions</b>	10.5"L x 8" W x 8.5" H
Air Volume (approximately)  80 CFM (varies with filter media)  Carbon Pre-filter + HEPA Filter - 100 FPM Carbon Pre-filter + Heavy Duty Carbon Filter - 60 FPM  115/1/60, 0.3 amps 220/1/50, 0.2 amps 8' grounded power cord with NEMA 5-15P plug  Sound Level  Maximum Temperature  Main Filter Options  Main Filter Options  Activated Carbon Specialty-blended Filter Media (i.e. acid gas, mercury, aldehyde, and ammonia)  Limited two-year warranty from date of shipment on	Blower Material	polyester epoxy coating
(approximately)  (varies with filter media)  Carbon Pre-filter + HEPA Filter - 100 FPM Carbon Pre-filter + Heavy Duty Carbon Filter - 60 FPM  115/1/60, 0.3 amps 220/1/50, 0.2 amps 8' grounded power cord with NEMA 5-15P plug  Sound Level 55 dba  Operating temperature not to exceed 170° F  HEPA (up to 99.97% efficient on particles down to 0.3 microns) ASHRAE (up to 95% efficient on particles down to 0.5 microns) ACTIVATE CARBON Specialty-blended Filter Media (i.e. acid gas, mercury, aldehyde, and ammonia)  Limited two-year warranty from date of shipment on		35 lbs
Inlet Velocities on High (approximately)  Filter – 100 FPM Carbon Pre-filter + Heavy Duty Carbon Filter – 60 FPM  115/1/60, 0.3 amps 220/1/50, 0.2 amps 8' grounded power cord with NEMA 5-15P plug  Sound Level 55 dba  Maximum Operating temperature not to exceed 170° F  HEPA (up to 99.97% efficient on particles down to 0.3 microns)  ASHRAE (up to 95% efficient on particles down to 0.5 microns)  Activated Carbon Specialty-blended Filter Media (i.e. acid gas, mercury, aldehyde, and ammonia)  Warranty (From Limited two-year warranty from date of shipment on		
Electrical  220/1/50, 0.2 amps 8' grounded power cord with NEMA 5-15P plug  Sound Level 55 dba  Operating temperature not to exceed 170° F  HEPA (up to 99.97% efficient on particles down to 0.3 microns)  ASHRAE (up to 95% efficient on particles down to 0.5 microns)  Activated Carbon Specialty-blended Filter Media (i.e. acid gas, mercury, aldehyde, and ammonia)  Limited two-year warranty from date of shipment on		Filter – 100 FPM Carbon Pre-filter + Heavy Duty Carbon Filter –
Maximum Temperature  Operating temperature not to exceed 170° F  HEPA (up to 99.97% efficient on particles down to 0.3 microns)  ASHRAE (up to 95% efficient on particles down to 0.5 microns)  Activated Carbon Specialty-blended Filter Media (i.e. acid gas, mercury, aldehyde, and ammonia)  Limited two-year warranty from date of shipment on		220/1/50, 0.2 amps 8' grounded power cord
Temperature  not to exceed 170° F  HEPA (up to 99.97% efficient on particles down to 0.3 microns)  ASHRAE (up to 95% efficient on particles down to 0.5 microns)  Activated Carbon Specialty-blended Filter Media (i.e. acid gas, mercury, aldehyde, and ammonia)  Limited two-year warranty from date of shipment on	Sound Level	55 dba
Main Filter Options  Main Filter Options  ASHRAE (up to 95% efficient on particles down to 0.5 microns) Activated Carbon Specialty-blended Filter Media (i.e. acid gas, mercury, aldehyde, and ammonia)  Limited two-year warranty from date of shipment on		
Warranty (From from date of shipment on		efficient on particles down to 0.3 microns)  ASHRAE (up to 95% efficient on particles down to 0.5 microns)  Activated Carbon  Specialty-blended Filter Media (i.e. acid gas, mercury, aldehyde, and
<b>Date of Shipment)</b> defects due to materials or workmanship.	Date of Shipment)	from date of shipment on defects due to materials
	Patent #	5,843,197