## **Model 400 Portable Floor Sentry**

# **Model # SS-400-PFS Product Specifications**

### **BASE UNIT DIMENSIONS**

22.5" Length, *Including Control Box* 20" Width 19.5" Height

### **ARM DIMENSIONS**

6" Dia., 72" Long Fire-Retardant Flex Arm (10.5" Dia. Round Hood)

### **CABINET MATERIAL**

16 ga. Carbon Steel

### WEIGHT

Approx. 50 lbs. - 100 lbs.

Varies Depending on Filter Media Installed

### **AIR VOLUME**

Variable Speed Control Standard on 115V 700 CFM High, Down to 50 CFM Low On/Off Toggle Switch Standard on 220V

### **ELECTRICAL**

115/1/60, 2.5 amps 220/1/50, 1.5 amps 8' grounded power cord with NEMA 5-15P Plug

### **SOUND LEVEL**

Approx. 60 dba @ 3'

### **FILTRATION**

**Depending on the Application:** 

- HEPA [up to 99.97% efficient on particles 0.3 microns and larger]
- ASHRAE [up to 95% efficient on particles 0.5 microns and larger]
- ACTIVATED CARBON
- SPECIALTY-BLENDED FILTER MEDIA [i.e. Acid Gas, Mercury, Aldehyde, Ammonia]

### WARRANTY

Limited two-year warranty from date of shipment on defects due to materials or workmanship. PATENT #5,843,197

# 19.5" Dimensions are Approximate Shown with Optional Accessories

6" Diameter, 72" L

### **Product Features**

- Variable Speed Controller Included (115V only)
- Portability Handle Included
- **Quiet Operation**

- Reliable, Low Maintenance Operation
- Self Supportive, Flexible Arm
- Simple, Quick "No Tool" Filter Change
- **Low Power Consumption**
- Optional Magnehelic Gage
- **Optional Hour Counter**

The **Portable Floor Sentry fume extractor** is used as a respiratory safety control for a variety of industrial applications that require the capture and filtration of airborne contaminants and chemical fumes. This source-capture fume extractor features quiet operation, a powerful fan, a flame-retardant and self-supportive flex arm, and a variety of high-quality filtration media.

Typical applications for this unit include: welding fume control, chemical fume extraction, solvent and epoxy fume control, particulate extraction, powder filling, soldering, light grinding, clean room applications, and a variety of applications involving chemical fumes and dust.

Several filter media options are available for this unit and include: HEPA filtration [up to 99.97% efficient on particles 0.3 microns and larger, ASHRAE filtration [up to 95% efficient on particles 0.5 microns and larger], Activated Carbon, and specialty-blended filter media [i.e. Acid Gas, Mercury, Aldehyde, Ammonia]. The Portable Floor Sentry allows multiple filter media to be housed inside the filter chamber for applications that emit both particulate and fume.

Other unit features include a variable speed controller, portability handle, 360-degree swivel arm, simple and quick "no-tool" filter change, and optional accessories including a magnehelic gauge, digital hour counter, and quick change pre-filter.

A smaller model [SS-300-PFS] and two larger models [SS-450-PFS & SS-500-BU-MP1] are also available



1.800.799.4609 www.sentryair.com sales@sentryair.com

